

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (4/98)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b))

Attorney Docket No. **679P05US**
First Inventor or Application Identifier
Title **Frequency Synthesizer**
Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ * Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Specification [Total Pages **20**]
(preferred arrangement set forth below)
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets **4**]
4. Oath or Declaration [Total Pages **2**]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 C.F.R. § 1.63(d))
(for continuation/divisional with Box 16 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b).

* NOTE FOR ITEMS 1 & 13: IN ORDER TO BE ENTITLED TO PAY SMALL ENTITY FEES, A SMALL ENTITY STATEMENT IS REQUIRED (37 C.F.R. § 1.27), EXCEPT IF ONE FILED IN A PRIOR APPLICATION IS RELIED UPON (37 C.F.R. § 1.28)

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

5. ☐ Microfiche Computer Program (Appendix)
6. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

7. ☐ Assignment Papers (cover sheet & document(s))
8. ☐ 37 C.F.R. § 3.73(b) Statement of Power of Attorney (when there is an assignee)
9. ☐ English Translation Document (if applicable)
10. ☐ Information Disclosure Statement (IDS)/PTO-1449 [Copies of IDS Citations]
11. ☐ Preliminary Amendment
12. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
13. ☐ * Small Entity Statement filed in prior application, (PTO/SB/09-12) Status still proper and desired
14. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
15. ☐ Other:

16. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment:
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____
Prior application information: Examiner _____ Group / Art Unit _____

For CONTINUATION or DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 4b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

17. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

or ☒ Correspondence address below

(Insert Customer No. or Attach bar code label here)

Name	Pascal & Associates			
Address	P.O. Box 11121 Station H			
City	Nepean	State	Ontario	Zip Code K2H 7T8
Country	Canada	Telephone	(613) 820-1366	Fax (613) 820-1553

Name (Print/Type)	Harold C. Baker	Registration No. (Attorney/Agent)	19333
Signature		Date	July 28, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

FREQUENCY SYNTHESIZERField of the Invention

5 The present invention relates to frequency synthesizers and more specifically, to frequency synthesizers which produce an output frequency higher than the input frequency.

Background of the Invention

10 In digital communications systems, it is often necessary to provide a clock signal with a frequency different from that of the available reference signal. This necessity may require independent crystal oscillators if both frequency sources need to be spectrally pure. However, independent crystal
15 oscillators increase the cost of the equipment and can cause problems if the crystal oscillators drift differently with age and temperature.

20 One approach to solving the above problem of different required frequencies is to synthesize a signal with a high frequency from a reference signal having a reference frequency.

25 Using well known phase locked loop (PLL) techniques, this high frequency is generated and is then divided into a lower desired frequency. Typically, the reference frequency is multiplied by an integer factor N to produce the high frequency and then divided by another integer factor M to obtain the desired
30 frequency. This method works well if the desired frequency is a convenient ratio of the reference frequency such as $1/2$, $3/2$, or $5/6$. However, if the desired frequency is not a convenient ratio of the

reference frequency, this method can prove cumbersome.
For example, if the desired frequency is 12 MHz and the
reference frequency is 19.68 MHz, the reference
frequency must be multiplied by $N=25$ and the resulting
frequency must be divided by $M=41$. The very high
frequency generated in this example would result in
higher power consumption for integrated circuits.

An alternative approach is to divide the
reference frequency and then multiply the divided
frequency to obtain the desired frequency. However,
this method has a significant drawback in that phase
noise is multiplied along with the divided frequency.

US Patent 3,976,945 provides yet another
alternative. This patent discloses performing a non
integer division of the input signal to obtain an output
signal with the desired frequency. However, in this case
the output frequency must necessarily be less than the
input frequency. If the desired frequency were higher
than the input frequency, this method would not be
applicable.

Accordingly, there is a need for a method and
an apparatus which can provide a desired output
frequency higher than the input frequency without the
power consumption and phase noise of the above methods.

Summary of the Invention

The present invention provides a method and
apparatus which provides a signal with an output
frequency higher than an input frequency. A phase
generator generates multiple phase signals from the
input signal with each phase signal having the same
frequency as the input signal but being out of phase
with the input signal by multiples of a set time

interval. These phase signals are transmitted to a multiplexer. The multiplexer output is determined by a select word generated by an accumulator from a stored value. The accumulator is clocked by the multiplexer output and the accumulator adds a control word with a set value to the stored value in the accumulator. This addition is accomplished at every cycle of the multiplexer output. By judiciously choosing control word and the time interval between phases, frequencies higher than the input frequency can be generated at the multiplexer output.

In a first embodiment, the present invention provides a frequency synthesizer for producing an output signal with an output frequency higher than an input frequency, the synthesizer comprising:

- a multiphase reference generator generating a plurality of phase signals having a reference frequency;

- a multiplexer coupled to receive the plurality of phase signals, the multiplexer having a multiplexer output signal based on at least one of the plurality of phase signals; and

- a phase selector coupled to receive the multiplexer output signal, the phase selector having a selector output which selects the multiplexer output signal;

wherein

- each phase signal is out of phase with the other phase signal by a multiple of a predetermined time interval,

- the selector output is received by the multiplexer means and

the multiplexer output is the output signal.

In a second embodiment, the present invention provides a frequency synthesizer comprising:

5 - a phase generator coupled to receive an input signal having a reference frequency and generating a plurality of phase signals having a frequency substantially equal to a reference frequency, each phase signal being out of phase with the input signal by a multiple of a predetermined time interval,

10 - a multiplexer means coupled to receive the plurality of phase signals and producing a multiplexer output,

 - a phase selector clocked by the multiplexer output and producing a selector output transmitted to the multiplexer means and

15 - a predetermined control word transmitted to the phase selector, the control word being added by the phase selector to a stored value on every cycle of the multiplexer output

wherein

20 - the multiplexer output is selected by the selector output and is based on at least one of the plurality of phase signals and

 - each successive multiplexer output leads its predecessor by a multiple of the predetermined time interval.

In a third embodiment, the present invention provides a method of synthesizing an output signal with an output frequency higher than a reference frequency from a plurality of phase signals having the reference frequency with each phase signal being out of phase with

adjacent phase signals by a multiple of a predetermined time interval, the method comprising:

- a) generating a select word from a stored value,
- b) selecting a selected phase signal from the plurality of phase signals based on at least a portion of the select word,
- c) generating an output signal from said selected phase signal,
- d) repeating steps a) to c) for every cycle of the output signal.

Description of the Figures

A better understanding of the invention may be obtained by reading the detailed description of the invention below, in conjunction with the following drawings, in which:

Figure 1 is a block diagram of a frequency synthesizer in accordance with the present invention;

Figure 2 is a block diagram of a first embodiment of the invention.

Figure 3 is a block diagram of a specific implementation of the embodiment illustrated in Fig 2.

Figure 4 is a timing diagram for the sixteen phase signals used in the embodiment in Figure 3;

Figure 5 is a block diagram of a second embodiment of the invention.

Description of the Preferred Embodiment

Referring to Figure 1, there is shown a block diagram of a frequency synthesizer 5. A multiphase reference generator 10 generates multiple phases 30 of a

signal with a reference frequency. These multiple phase signals 30 are sent to a multiplexer 40. The output 50 of the multiplexer 40 serves as both the output signal and as the clock of a phase selector 60. The phase selector 60 receives a control word 70 at port IN. A portion of the selector output 80 of the phase selector 60 is used as a SELECT signal for the multiplexer 40. The SELECT signal is used to select which one of the multiple phase signals 30 is used as the output 50 of the multiplexer 40.

Referring to Figures 2 and 3, a specific embodiment of the invention is illustrated. In this embodiment, the multi-phase reference generator is comprised of a reference signal 90 being sent to a phase generator 100. The phase generator 100 generates multiple phase signals 30 from the reference signal 90 and the multiple phase signals 30 are sent to the multiplexer 40. The input signal 90 has a reference frequency of 19.86 MHz and the phase generator 100 generates 16 phase signals 30A-30P. (see Figure 3) These phase signals are sent to a 16:1 multiplexer, (MUX) 40A. The 16:1 MUX 40A selects one of the its sixteen phase signals 30A-30P based on the input to select port 42. The numbers in the block 40A refer to the select values required at the select port 42 to select the phase signal. Thus, to select OUT11 (phase signal 30F), a binary value of 101 (decimal value 5) must be inputted to the select port 42. The MUX 40A output 50 is used to clock a 20 bit accumulator 60A which serves as the phase selector 60. The accumulator 60A is fed a control word 70 which the accumulator 60A adds to a stored value on every cycle of the MUX output 50.

The input to the select port 42 is a portion of the selector output 80. In this case the 4 most significant bits (MSB) of the selector output 80 serves as the select word 110 sent to select port 42.

The selector output 80 is the binary value of the stored value in the accumulator 60A, a binary digital accumulator. Thus, if the selector output 80 has a decimal value of 9001 and the control word 70 has a decimal value of 10, on the next cycle of the MUX output 50 the selector output 80 becomes $9001+10=9011$ (decimal value) as the control word is added to the stored value, thereby changing the selector output 80. In other words, the accumulator adds a control word X to a stored value Y_0 to produce a new stored value Y_1 on each cycle of the selected phase signal (any one of 30A-30P). So, for every cycle of the selected phase signal, a new stored value Y_1 is determined by

$$Y_1 = X + Y_0 \quad (1)$$

where Y_0 is the previous stored value. When the accumulator 60A overflows, it produces a stored value

$$Y_1 = X + Y_0 - K \quad (2)$$

where K is the maximum value which the accumulator can store. If the control word X is negative, then the new stored value becomes

$$Y_1 = X + Y_0 + K \quad (3)$$

This is how most currently known binary digital accumulators handle overflow. It should be noted that, by varying the control word X, the frequency of the output signal 50 can be varied. Thus, the value of the control word X effectively controls the frequency of the output signal 50.

Regarding the phase generator 100, the phase signals 30A-30P it produces all have the same frequency as the input or reference signal 90. However, each phase signal 30A-30P is out of phase with the reference signal 90 by a time value which is a multiple of a set time interval. For this example, the set time interval is

$$\frac{1}{(16 \times 19.86 \text{ MHz})} = 3.176 \text{ ns.} \quad (4)$$

Thus, OUT1 in Figure 2 would be 3.176ns later than the reference signal, OUT2 would be 3.176ns x 2 later than the reference signal and 3.176ns later than OUT1. To best illustrate this, Figure 4 shows the timing diagrams of the phase signal OUT1-OUT16 along with the reference signal REF. It should be noted that in Figure 4, each division in the time axis (horizontal axis) represents 3.176 ns.

From the above, the required set time interval between phase signals for a given number of phase signals and reference frequency can be generalized to be:

$$\text{Set Time Interval} = \frac{1}{(\text{number of phase signals}) \times (\text{reference frequency})} \quad (5)$$

The phase generator 100 can be a multiple stage Johnson counter - in this case it would be an 8 stage Johnson counter. The phase generator 100 can also be a delay lock loop (DLL) circuit. Alternatively, the multiple phase signals can be generated by a ring oscillator.

To assure trouble free operation and to obtain higher output frequencies, the phase selector 60 (as embodied by the accumulator 60A) should select progressively earlier phase signals rather than progressively later phase signals. This means that each successive phase signal should lead its predecessor phase signal by a multiple of the set time interval. This provides a shorter cycle time for the MUX output 50 than the input or reference signal, thereby obtaining a higher frequency.

To best illustrate the workings of the synthesizer, the following example is provided:

The output frequency of the synthesizer is given by

$$f_{out} = \frac{f_{ref}}{(1 - \frac{x}{2^n})} \quad (6)$$

where f_{out} is the output frequency, f_{ref} is the frequency of the 16 phase reference, X is the control word controlling the accumulator and n is the number of bits in the accumulator. For a 20 bit accumulator with a 24 MHz selected output frequency and a 19.68 MHz reference frequency, the correct value of X is, from Equation 6, 188744. For example, if the initial state of the

accumulator, Y , is 0, then the subsequent states resulting from subsequent cycles of the selected output will be, using Equation 1, 188744, 377488, 566232, 754976 and 943720. On the next selected output cycle, the accumulator will overflow giving, from Equation 2, $11322464-2^{20}=83888$ (decimal).

The four MSBs of these accumulator states form the numbers 0 for the initial state then, 2, 5, 8, 11, 14. After the overflow, the four MSBs form the number 1. This output sequence should in turn select OUT16, as the initial phase, then OUT14, OUT11, OUT8, OUT5, OUT2, and after the overflow, OUT15. These results are summarized in Table 1 below:

Table 1

Previous Accumulator State (Y_0 in decimal)	Current Accumulator State (Y_1 in decimal)	4 MSBs of Current Accumulator State (Y_1) in binary	4 MSBs of Current Accumulator State (Y_1) in decimal	Phase Chosen
-	0	0000	0	OUT16
0	188744	0010	2	OUT14
188744	377488	0101	5	OUT11
377488	566232	1000	8	OUT8
566232	754976	1011	11	OUT5
754976	943720	1110	14	OUT2
943720	83888	0001	1	OUT15

Although the long term accuracy of the synthesizer is limited only by the accuracy of the reference and the number of bits in the accumulator, the synthesizer will have a periodic jitter whose amplitude will be at least one-half the time interval between

phase signals. Increasing the number of phase signals will reduce this time interval. The error is slightly more than one-half the time interval between phases because the interval between phases will not be exactly the same once imperfections in the delay elements are taken into account. These delay elements form the multiphase reference for producing the different phase signals and can be a Johnson counter, frequency divider, or a ring oscillator.

It should be noted that the parameters of the embodiments described above can be extended. Specifically, the number of phase signals is not constrained to 16. If the number of phase signals to choose from can be extended to a number which is a higher power of 2 (i.e. 32, 64, etc.), then the accumulator need not be changed. It is apparent that the multiplexer would have to be capable of handling the number of phase signals available. Also, instead of only using the 4 MSBs of the selector output 80, more bits would have to be included in the select word.

However, while the above contemplates using a number of phase signals which is an even power of 2, the design can be further extended to phase signals which are not an even power of 2. As an example, if the number of phase signals was 20, two possible routes can be taken to implement the invention. Specifically, the accumulator can be designed to overflow at a multiple of 20 where the multiple is a "round" binary number such as 2, 4, 8 etc. The 5 MSBs can then be used to select one of the 20 phase signals. The 5 MSBs could be constrained to be in the range from 0 to 19 by suitable logic gating.

It should also be noted that the phase generator and the phase selector need not be completely separate. Figure 5 illustrates an embodiment which uses 64 phase signals but does not require that all 64 phase signals be generated. The 64 phase signals are derived from only 16 phase signals.

In the embodiment of Figure 5, the multiplexer comprises a 16 x 2 multiplexer 40B and a blender/interpolator circuit 40C. The 16 x 2 multiplexer 40B selects two of the 16 phase signals based on a portion of the select word 110. The blender/interpolator circuit 40C is a 4 phase to 1 phase interpolator circuit which can generate specific delays between its inputs. The phase generator 100 and the accumulator 60A remain the same as shown in Figures 2 and 3. However, instead of only using the 4 MSBs of the selector output 80 as the select word 110, 6 MSBs are used. The added 2 MSBs are used to control the blender/interpolator circuit 40C.

In Figure 5, rather than selecting a single phase signal, two adjacent phase signals are selected by the four MSBs (bits 19 to 16) of the selector output 60A. These two selected phase signals are then blended or interpolated to produce a phase signal (the MUX output) with some fixed delay plus an additional variable delay that is a portion of the delay between the two selected phase signals. The variable delay is controlled by the two LSBs (bits 15 and 14) of the six MSBs (bits 19 to 14) of the accumulator output 80.

It is important to have the control of the blending circuit 40B provide the same result as if the six bit select sort were directly controlling a 64 phase reference. To provide this result, with the four bit

select word values of 0 to 15 (of bits 19-16) selecting phases OUT1 to OUT16 respectively, the 2 bit select word values of 0 to 3 (of bits 15-14) should respectively select increasing variable delays.

A person understanding the above-described invention may now conceive of alternative designs, using the principles described herein. All such designs which fall within the scope of the claims appended hereto are considered to be part of the present invention.

5

I claim:

1. A frequency synthesizer for producing an output signal with an output frequency higher than an input frequency, the synthesizer comprising:

5 - a multiphase reference generator generating a plurality of phase signals having a reference frequency;

10 - a multiplexer coupled to receive the plurality of phase signals, the multiplexer having a multiplexer output signal based on at least one of the plurality of phase signals; and

15 - a phase selector coupled to receive the multiplexer output signal, the phase selector having a selector output which selects the multiplexer output signal;

wherein

- each phase signal is out of phase with the other phase signal by a multiple of a predetermined time interval,

20 - the selector output is received by the multiplexer and

the multiplexer output is the output signal.

2. A frequency synthesizer as in claim 1 wherein the multiplexer output is chosen from the plurality of phase signals and a new phase signal is chosen as the multiplexer output by the phase selector on the occurrence of either a rising edge of the multiplexer output or a falling edge of the multiplexer output.

3. A frequency synthesizer as in claim 2 wherein each successive phase signal chosen by the phase selector leads its predecessor by a multiple of the predetermined time interval.

4. A frequency synthesizer as in claim 3 wherein the multiphase reference generator is a phase generator coupled to receive a reference signal having the reference frequency and wherein the plurality of phase signals is based on the reference signal.

5. A frequency synthesizer as in claim 4 wherein the phase generator is chosen from the group comprising:

- a ring oscillator;
- a Johnson counter circuit; and
- a delay locked loop circuit.

6. A frequency synthesizer as in claim 5 wherein the multiplexer selects one out of a plurality of possible phase signals from the phase generator as the multiplexer output based on a select word.

7. A frequency synthesizer as in claim 6 wherein the phase selector is a binary digital accumulator clocked by the multiplexer output.

8. A frequency synthesizer as in claim 7 wherein the binary digital accumulator adds a predetermined binary control word to a binary stored value on each cycle of the multiplexer output, and wherein selected bits of the binary stored value forms the selector output.

9. A frequency synthesizer as in claim 8 wherein the selector output is transmitted to the multiplexer as the select word.

10. A frequency synthesizer as in claim 1 wherein the multiplexer output is produced from at least two phase signals chosen from the plurality of phase signals.

11. A frequency synthesizer as in claim 10 wherein each successive multiplexer output determined by the selector output leads its predecessor by a multiple of the predetermined time interval.

12. A frequency synthesizer as in claim 11 wherein the multiphase reference generator is a phase generator coupled to receive a reference signal having the reference frequency and wherein the plurality of phase signals is based on the reference signal.

13. A frequency synthesizer as in claim 12 wherein the phase generator is chosen from the group comprising:

- a ring oscillator;
- a Johnson counter circuit; and
- a delay locked loop circuit.

14. A frequency synthesizer as in claim 11 wherein the multiplexer comprises:

- a multiplexer circuit which selects at least two selected phase signals out of the plurality of phase signals; and

a signal blender/interpolator coupled to receive the selected phase signals from the multiplexer, the signal blender/interpolator producing the multiplexer output; and

10 wherein

the signal blender/interpolator blends the selected phase signals to produce the multiplexer output, and

15 at least two selected phase signals are selected based on a portion of a select word.

15. A frequency synthesizer as in claim 14 wherein the multiplexer output includes a variable delay determined by a delay between the selected phase signals and a first portion of the select word.

16. A frequency synthesizer as in claim 14 wherein the phase selector is a binary digital accumulator clocked by the multiplexer output.

17. A frequency synthesizer as in claim 16 wherein the binary digital accumulator adds a predetermined binary control word to a binary stored value on each cycle of the multiplexer output, and
5 wherein selected bits of the binary stored value forms the selector output.

18. A frequency synthesizer as in claim 17 wherein the selector output is transmitted to the multiplexer means as the select word.

19. A frequency synthesizer comprising:

- a phase generator coupled to receive an input signal having a reference frequency and generating a plurality of phase signals having a frequency substantially equal to a reference frequency, each phase signal being out of phase with the input signal by a multiple of a predetermined time interval,

- a multiplexer means coupled to receive the plurality of phase signals and producing a multiplexer output,

- a phase selector clocked by the multiplexer output and producing a selector output transmitted to the multiplexer means and

- a predetermined control word transmitted to the phase selector, the control word being added by the phase selector to a stored value on every cycle of the multiplexer output wherein

- the multiplexer output is selected by the selector output and is based on at least one of the plurality of phase signals and

- each successive multiplexer output leads its predecessor by a multiple of the predetermined time interval.

20. A method of synthesizing an output signal with an output frequency higher than a reference frequency from a plurality of phase signals having the reference frequency with each phase signal being out of phase with adjacent phase signals by a multiple of a predetermined time interval, the method comprising:

a) generating a select word from a stored value,

10 b) selecting a selected phase signal from the
plurality of phase signals based on at least a portion
of the select word,
 c) generating an output signal from said
selected phase signal,
15 d) repeating steps a) to c) for every cycle of
the output signal.

21. A method as claimed in claim 20 further
including the step of generating the plurality of phase
signals.

22. A method as claimed in claim 20 wherein
each successive output signal leads its predecessor by a
multiple of the predetermined time interval.

23. A method as in claim 20 wherein step b)
includes selecting at least two selected phase signals
from the plurality of phase signals based on at least a
portion of the select word.

24. A method as in claim 23 wherein step c)
includes blending the at least two selected phase
signals to produce the output signal.

25. A method as in claim 20 wherein step a)
includes adding a predetermined control word to the
stored value to produce a new stored value.

[illegible][illegible]




FIG 1






FIG 2








FIG 5

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)

Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION FOR UTILITY OR DESIGN PATENT APPLICATION (37 CFR 1.63)	Attorney Docket Number	679P05US
	First Named Inventor	Riley
	COMPLETE IF KNOWN	
	Application Number	/
	Filing Date	
	Group Art Unit	
<input checked="" type="checkbox"/> Declaration Submitted with Initial Filing	OR	<input type="checkbox"/> Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)
Examiner Name		

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

FREQUENCY SYNTHESIZER

the specification of which *(Title of the Invention)*

☒ is attached hereto
OR
☐ was filed on (MM/DD/YYYY) as United States Application Number or PCT International Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto:

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below:

Application Number(s)	Filing Date (MM/DD/YYYY)

☐ Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☒ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
Label here

Name	Registration Number	Name	Registration Number
R.A. Wilkes	28170		
H.C. Baker	19333		
R.G. Hendry	22927		

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number or Bar Code Label

OR ☒ Correspondence address below

Name	Pascal & Associates				
Address	P.O. Box 11121				
Address	Station H				
City	Nepean	State	Ontario	ZIP	K2H 7T8
Country	Canada	Telephone	(613) 820-1366	Fax	(613) 820-1553

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle [if any])	Family Name or Surname
Thomas Atkin Denning	RILEY

Inventor's Signature				Date	7/27/00
Residence: City	Osgoode	State	ON	Country	Canada
Post Office Address	3356 Leroy Street				
Post Office Address	<i>Thomas Riley</i>				
City	Osgoode	State	ON	ZIP	K0A 2W0
				Country	Canada

☐ Additional inventors are being named on the supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto